

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Switch Mode Power Supply

Name and address of the applicant

EGSTON System Electronics Eggenburg GmbH
Grafenberger Strasse 37, 3730 Eggenburg, Austria

Name and address of the manufacturer

EGSTON System Electronics Eggenburg GmbH
Grafenberger Strasse 37, 3730 Eggenburg, Austria

Name and address of the factory

Egston System Electronic spol.s.r.o.
Průmyslova 20, Znojmo, CZ-67015, Czech Republic*Note: When more than one factory, please report on page 2* Additional Information on page 2

Ratings and principal characteristics

See page 2.

Trademark (if any)



Customer's Testing Facility (CTF) Stage used

\

Model / Type Ref.

Power supply unit: P2xyzW3q
Charger: C2xyzW3q
(see page 2 for details)

Additional information (if necessary may also be reported on page 2)

This CB test certificate substitutes previously issued CB test certificate No. SI-4077, issued on 2013-12-20, due to update of test report.

 Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 60601-1:2005 + A1:2012

As shown in the Test Report Ref. No. which forms part of this Certificate

T223-0119/19, issued on 2019-04-10.

This CB Test Certificate is issued by the National Certification Body

SIQ Ljubljana, Tržaška cesta 2, SI-1000 Ljubljana, Slovenia
T +386 1 4778 100, F +386 1 4778 444, info@siq.si, www.siq.si

SIQ Ljubljana is accredited by Slovenian Accreditation with accreditation number CP-001 in the field of certification of products, processes and services.

Date: 2019-04-10

Signature: Bojan Pečavar

Name and address of the factory

- 1) EGSTON System Electronic spol.s.r.o.
Průmyslova 20, Znojmo, CZ-67015, Czech Republic
- 2) EGSTON Electronics Zhuhai Ltd.
3/F, No. 3 Pinggong No. 1 Road, Nanping Technology Ind. Park, Zhuhai City, China

Ratings and principal characteristics

Input:

12 W models: 100-240 Vac; 50-60 Hz; 260-120 mA

24 W models: 100-240 Vac; 50-60 Hz; 480-200 mA

Output:

Power supply units (12 W): 4,5-24 Vdc; Max. 2,4 A; Max. 12 W

Power supply units (24 W): 5-24 Vdc; Max. 3,0 A; Max. 24 W

Chargers (12W): 4,2-25,5 Vdc; Max. 2,4 A; Max. 12 W

Chargers (24 W): 4,2-25,5 Vdc; Max. 2,5 A; Max. 24 W

Model / Type Ref.:

Power supply unit: P2xyzW3q

Charger: C2xyzW3q

Where "2" defined operation temperature and can be any numeric character specifying temperature ranges within the approved range

Where "x" defined different primary connector and can be E (Euro plug), U (US/Japan/Canada plug), G (United Kingdom plug), D (Desktop module), P (Circuit Board Module), S (Short desktop), C (Changeable plug housing), O (Open frame) or A (Australia plug)

Where "y" defined cable connection and can be F (Fixed connection) or S (Detachable connection)

Where "z" defined different application and can be S (standard), M (Medical) or H (Household)

Where "W" defined input range and can be any numeric character specifying an input voltage range within the approved range

Where "3" defined output stability and can be any numeric character specifying a tolerance in %

Where "q" defined optional and can be L (Power on LED), C (Current regulation) or D (Current detection)

Additional information (if necessary)

Date: 2019-04-10

Signature: Bojan Pečavar

