

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	Power supply
Name and address of the applicant	EGSTON System Electronics Eggenburg GmbH Grafenberger Strasse 37, 3730 Eggenburg, Austria
Name and address of the manufacturer	EGSTON System Electronics Eggenburg GmbH Grafenberger Strasse 37, 3730 Eggenburg, Austria
Name and address of the factory	See page 2
<i>Note: When more than one factory, please report on page 2</i>	<input checked="" type="checkbox"/> Additional Information on page 2
Ratings and principal characteristics	See page 2
Trademark / Brand (if any)	EGSTON
Customer's Testing Facility (CTF) Stage used	/
Model / Type Ref.	E2xFzWy 24; E2xFzWy 30
Additional information (if necessary may also be reported on page 2)	See page 2
A sample of the product was tested and found to be in conformity with	<input checked="" type="checkbox"/> Additional Information on page 2 IEC 61558-2-16:2009 + A1:2013 IEC 61558-1:2017
As shown in the Test Report Ref. No. which forms part of this Certificate	T211-0363/21 (2021-05-05)


This CB Test Certificate is issued by the National Certification Body

SIQ Ljubljana, Mašera-Spasičeva ulica 10, SI-1000 Ljubljana, Slovenia
T +386 1 4778 100, F +386 1 4778 444, info@siq.si, www.siq.si

SIQ Ljubljana is accredited by Slovenian Accreditation with accreditation number CP-001 in the field of certification of products, processes and services.

Date: 2021-05-05

Signature: Bojan Pečavar



Name and address of the factories:

- 1) EGSTON System Electronic spol.s.r.o., Průmyslová 20, 670 15 Znojmo, Czech Republic
- 2) EGSTON Electronics Zhuhai Ltd. 3/F, No. 3 Pinggong No. 1 Road, Nanping Technology Ind. Park, Zhuhai City, China

Ratings and principal characteristics:**E2xFzWy 24**

Input: 100-240 Vac; 50-60 Hz; 490 mA

Output voltage: 5-24 Vdc

Output current: Max. 3,0 A

Output power: Max. 24 W

Where "x" can be:

E= Euro Plug-in

U= US, Canada Plug-in

G= United Kingdom Plug-in

C= Changeable Plug

Where "y" can be 1 or 3 to denote output tolerance in %

Where "z" can be:

S= Standard power supply

M= Medical power supply

H= Household power supply

(There is no technical differences between those 3 models)

E2xFzWy 30

Input: 100-240 Vac; 50-60 Hz; 590 mA

Output voltage: 5-24 Vdc

Output current: Max. 3,0 A

Output power: Max. 30 W

Where "x" can be:

E= Euro Plug-in

U= US, Canada Plug-in

G= United Kingdom Plug-in

A= Australia Plug-in

C= Changeable Plug

D= Desktop

S= Cable-cable

P= PCB Module

O= Open Frame Version

T= Terminal Version

Where "y" can be 1 or 3 to denote output tolerance in %

Where "z" can be:

S= Standard power supply

M= Medical power supply

H= Household power supply

(There is no technical differences between those 3 models)

Additional information (if necessary)

This CB Certificate replaces previously issued CB Certificate No. SI-5808 M1, dated on 2017-07-11, due to issued new test report.

Date: 2021-05-05

Signature: Bojan Pečavar

